

Construction

Technical Data Sheet

Acronal[®] S 734 P



Chemical Nature Re-dispersible polymer powder based on an aqueous, plasticizer-free, APEO free, anionic copolymer dispersion of acrylic acid ester and styrene.

Properties

Typical Properties

Solids content,	%	ca. 99
pH (30% solution)		ca. 7 – 9

Other properties

Appearance		off white to yellowish
Form		powder, free flowing
Bulk density,	kg/m ³	ca. 500
Tg		°C ca. +20

*These figures should be taken for comparison purposes only. All that can be obtained from it is an idea of the order of magnitude.

Area of application

Applications

Acronal[®] S 734 P is used to improve and increase the flexibility, flexural strength, adhesion, abrasion resistance and water resistance of one-component, drymix construction products based on hydraulic cements. Acronal[®] S 734 P is defoamed, effective in low w/c ratio formulations and is APEO free.

Acronal[®] S 734 P is used in one-component, drymix, flexible, Self Leveling Underlayments, Concrete Repair Mortars and products that need rapid polymer redispersibility for high polymer content, minimal slake time and less sticking to tools.

Processing

Typical dosage rate is 1 to 5% by weight of cement.

Dry mortars that contain Acronal[®] S 734 P can be dry mixed with typical mixing equipment. Because the product is thermoplastic care must be taken to ensure that there is not excessive heat exposure.

Acronal[®] S 734 P is compatible with typical water reducers, rheology modifiers and defoamers such as Melment[®], Melflux[®], Starvis[®] and Vinapor[®].

Construction products containing Acronal[®] S 734 P may discolor on exposure to sunlight, color stability should be evaluated.

Safety

General

The usual precautions when handling chemicals must be observed. This includes compliance with Federal, State and Local health and safety regulations, ventilation, protective clothing and goggles.

Safety Data Sheet

All safety information is provided in the Safety Data Sheet for Acronal® S 734 P.

Storage

Acronal® S 734 P has a shelf life of 12 months from delivery date when stored cool, dry, in the original packaging and pallets are not double stacked. Heat, moisture and pressure may cause lumps to form.

Important

The descriptions, designs, and data contained herein are presented for your guidance only. Because there are many factors under your control which may affect processing or application/use it is necessary for you to make appropriate tests to determine whether the product is suitable for your particular purpose prior to use. **NO WARRANTIES OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, OR DATA MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, DATA OR DESIGNS PROVIDED BE PRESUMED TO BE A PART OF OUR TERMS AND CONDITIONS OF SALE.** Further, you expressly understand and agree that the descriptions, designs, and data furnished by BASF hereunder are given gratis and BASF assumes no obligation or liability for same or results obtained from use thereof, all such being given to you and accepted by you at your risk.

Acronal is a registered trademark of BASF Group.

© BASF Corporation, 2015



BASF Corporation is fully committed to the Responsible Care® initiative in the USA, Canada, and Mexico.

For more information on Responsible Care® go to:

U.S.: www.basf.us/responsiblecare_usa

Canada: www.basf.us/responsiblecare_canada

México: www.basf.us/responsiblecare_mexico

BASF Corporation
Dispersions and Pigments
11501 Steele Creek Road
Charlotte, North Carolina 28273
Phone: (800) 251 – 0612
Email: edtech_info@basf.com
www.basf.us/dpsolutions