

Foamaster[®] MO 2157

Product description Foamaster[®] MO 2157 is an emulsified defoamer, designed for water- based systems, especially high PVC decorative paints.

Key benefits

- Excellent defoamer action in High PVC paints
- Excellent de-aeration action
- Good substrate wetting
- Helps levelling
- Easy incorporation
- Excellent price/performance

Chemical nature Blend of emulsified mineral oil, hydrophobic solids and foam killer polymers.

Properties

Appearance Opaque, white liquid

Technical data (no supply specification)	Density	25 °C	0.90 – 1.00 g/cm ³
	pH (as is)	25 °C	6.5 – 9.5
	Viscosity (Brookfield)	RVT, f3, 50rpm, 25°C	500 – 2000 mPa.s

Application

Formulation guideline

Foamaster® MO 2157 is an emulsified defoamer especially developed to decorative paints with high PVC, as economic paints and texture and plasters also.

Dosage

0.2 – 0.8% on the total formulation. Despite of the recommended dosage, laboratory tests are advised. The addition could be in grind stage or in letdown portion, however, for better grinding efficiency, it is advisable to add a portion (~ 70%) of the total defoamer in the grinding and the rest in the letdown stage.

Storage

Foamaster® MO 2157 is subject to appropriate storage under the usual storage and temperature conditions, our products are durable for at least 1 year. Keep it at original package (preferably between 5 and 45°C) in a dry place, under protection from the weather. Foamaster® MO 2157 can show a slight phase separation with time. Stir well before using. This does not change the characteristics and performance of the product.

Contacts worldwide

Asia
BASF East Asia Regional Headquarters Ltd
45/F, Jardine House
No. 1 Connaught Place
Central Hong Kong
China
formulation-additives-asia@basf.com

North America
BASF Corporation
11501 Steele Creek Road
Charlotte, NC 28273
USA
formulation-additives-nafta@basf.com

Europe
BASF SE
Formulation Additives
67056 Ludwigshafen
Germany
formulation-additives-europe@basf.com

South America
BASF S.A
Rochaverá - Crystal Tower
Av. das Nações Unidas, 14.171
Morumbi - São Paulo-SP
Brazil
formulation-additives-south-america@basf.com

Validity

This Technical Data Sheet is valid for all versions of the Foamaster® MO 2157.

Safety

When handling this product, please comply with the advice and information given in the safety data sheet and observe protective and workplace hygiene measures adequate for handling chemicals.

Note

The data contained in this publication are based on our current knowledge and experience. In view of the many factors that may affect processing and application of our product, these data do not relieve processors from carrying out their own investigations and tests; neither do these data imply any guarantee of certain properties, nor the suitability of the product for a specific purpose. Any descriptions, drawings, photographs, data, proportions, weights, etc. given herein may change without prior information and do not constitute the agreed contractual quality of the product. The agreed contractual quality of the product results exclusively from the statements made in the product specification. It is the responsibility of the recipient of our product to ensure that any proprietary rights and existing laws and legislation are observed.

® = Registered trademark

™ = Trademark of the BASF Group, unless otherwise noted

www.basf.com/formulation-additives