

Formulation Additives

Technical Data Sheet

Loxanol[®] CA 5310

(old: Loxanol[®] EFC 100)



Product Description

Loxanol[®] CA 5310 Emission Free Coalescent was developed for coatings formulations with less than 50 g/l VOC. It is produced from renewable raw materials and can replace traditional VOC contributing coalescent.

Traditional coalescent vaporize in the air during the drying process and contribute towards VOC (Volatile Organic Compounds). However, Loxanol[®] CA 5310 remains in the paint film to provide a long lasting coalescing effect and at the same time increasing the total solids content of the system.

Loxanol[®] CA 5310 is supplied as a 100% active pale yellow liquid.

Loxanol[®] CA 5310 not only reduces the VOCs of the paint, but also improves key performance properties.

Chemical Composition

Produced from renewable raw materials, it can replace traditional VOC contributing coalescent.

Properties

Product Specifications

Appearance	Clear to slightly hazy, yellow liquid
Viscosity (ISO 2555)	25 – 35 mPa s
Acid value, meq (ISO 660)	5 max. KOH/g
Saponification value (ISO 3657)	165 – 170
Density (25° C) (ISO 2811-3)	0.89 – 0.92 g/ml
Moisture (%) (Water content acc. to Karl Fischer) (ISO 4317)	0 – 0.30

Typical Characteristics

Activity, %	100
Color, Gardner (ISO 4630)	6 max.
Acid Value	5
Moisture	0.01 %

These typical values should not be interpreted as specifications.

Applications

Loxanol[®] CA 5310 has the following key performance properties:

- Does not contribute to the VOC content of the paint
- Low odor
- Improved scrub resistance
- Good low-temperature cure
- Higher gloss values
- Improved Rheology modifier efficiency
- Good color acceptance / color development
- Non-yellowing
- Non-hazardous and based on renewable resources

Loxanol[®] CA 5310 is recommended for use in Architectural Coatings, Industrial Coatings, Construction and Building Products. We expect to find more utility for Loxanol[®] CA 5310 in other areas requiring an efficient coalescent.

Dosage

Loxanol[®] CA 5310 at a level of 1 percent to 2 percent, based on total paint, provides a good balance of performance and application properties. We recommend determining the optimum level of Loxanol[®] CA 5310 to achieve the desirable performance.

The optimum level can be determined by the minimum film formation temperature (MFFT) bar. Loxanol[®] CA 5310 can be blended with other coalescent to optimize the balance between VOC and desired performance.

Safety

General

The usual safety precautions when handling chemicals must be observed. These include the measures described in Federal, State, and Local health and safety regulations, thorough ventilation of the workplace, good skin care, and wearing of protective goggles.

Material Safety Data Sheet

All safety information is provided in the Material Safety Data Sheet for Loxanol[®] CA 5310.

Storage

Loxanol[®] CA 5310 is subject to appropriate storage under the usual storage and temperature conditions; our products are durable for at least 2 years. Loxanol[®] CA 5310 is packaged in 55 gallon (200 liter) open-head, polyethylene / fiber composite drums. Storage in a cool, dry place away from direct heat is recommended. If Loxanol[®] CA 5310 was subjected to freezing temperatures during storage, warm to room temperature and mix thoroughly before using.

Important

While the descriptions, designs, data and information contained herein are presented in good faith and believed to be accurate, they are provided for guidance only. Because many factors may affect processing or application/use, BASF recommends that the reader make tests to determine the suitability of a product for a particular purpose prior to use. **NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESCRIPTIONS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS.** In no case shall the descriptions, information, data or designs provided be considered a part of BASF's terms and conditions of sale. Further, the descriptions, designs, data, and information furnished by BASF hereunder are given gratis and BASF assumes no obligation or liability for the descriptions, designs, data or information given or results obtained all such being given and accepted at the reader's risk.

Loxanol is a registered trademark of BASF Group.

© BASF Corporation, 2013



BASF Corporation is fully committed to the Responsible Care[®] initiative in the USA, Canada, and Mexico.

For more information on Responsible Care[®] goto:

U.S.: www.basf.us/responsiblecare_usa

Canada: www.basf.us/responsiblecare_canada

México: www.basf.us/responsiblecare_mexico

BASF Corporation
Dispersions and Pigments
11501 Steele Creek Road
Charlotte, North Carolina 28273
Phone: (800) 251 – 0612
Email: edtech_info@basf.com
www.basf.us/dpsolutions