

Styrofan[®] NX 1492

Chemical Nature **Aqueous carboxylated styrene-butadiene copolymer dispersion for use in waterproofing applications**

Properties

Typical Properties

Solids content	%	49.0 – 51.0
pH		8.0 – 9.0

Other properties of the dispersion

Density	g/cm ³ lbs/gal	ca. 1.00 ca. 8.3
Viscosity at 23 °C (Brookfield RV, Spindle #2, at 100 rpm)	cps	ca. 200
Average particle size	µm	ca. 0.2
Film-forming temperature	°C	<1 min.
Dispersion type		anionic
Plasticizer content		plasticizer-free
Antioxidant		non-staining
Sensitivity to freezing	°C	do not freeze
Inorganic filler compatibility		good

Properties of the film

Glass transition temperature(Tg)	°C	ca. -10
Density	g/cm ³	ca. 1.00
Mechanical properties* at 23 °C		
Tensile strength	psi	ca. 250
Elongation at break	%	ca. 625
Surface tack		slight

Application

Fields of application

Styrofan NX 1492 is used for coating green concrete (blocks, moldings and in-situ concrete), and acts as a humectant. If it is used as a curing agent, it prevents premature drying of green concrete. Styrofan NX 1492 forms films with excellent water resistance and very good MVT values for barrier coatings over concrete.

Styrofan NX 1492 has good compatibility with inorganic fillers, therefore allowing for easier formulating and compounding where desired.

It is usually necessary to disperse the fillers and pigments with sufficient wetting and dispersing.

Safety

General

The usual safety precautions when handling chemicals must be observed. These include the measures described in Federal, State and Local health and safety regulations, thorough ventilation of the workplace, good skin care and wearing of protective goggles.

Safety Data Sheet

All safety information is provided in the Safety Data Sheet for Styrofan NX 1492.

Storage

Please refer to the "Handling and Storage of Polymer Dispersions" brochure.

Important

The descriptions, designs, and data contained herein are presented for your guidance only. Because there are many factors under your control which may affect processing or application/use it is necessary for you to make appropriate tests to determine whether the product is suitable for your particular purpose prior to use. **NO WARRANTIES OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, OR DATA MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, DATA OR DESIGNS PROVIDED BE PRESUMED TO BE A PART OF OUR TERMS AND CONDITIONS OF SALE.** Further, you expressly understand and agree that the descriptions, designs, and data furnished by BASF hereunder are given gratis and BASF assumes no obligation or liability for same or results obtained from use thereof, all such being given to you and accepted by you at your risk.

Styrofan is a registered trademark of BASF Group.

© BASF Corporation, 2020



BASF Corporation is fully committed to the Responsible Care® initiative in the USA, Canada, and Mexico. For more information on Responsible Care® go to:
U.S.: www.basf.us/responsiblecare_usa
Canada: www.basf.us/responsiblecare_canada
México: www.basf.us/responsiblecare_mexico

BASF Corporation
Dispersions and Resins
11501 Steele Creek Road
Charlotte, North Carolina 28273
Phone: (800) 251 – 0612
Email: CustCare-Charlotte@basf.com
Email: edtech-info@basf.com
www.basf.us/formulation-additives