

# Bíosilico. CS.PC.5299

# **Premium Additive for Multiple applications**

**Bíosilico**. **CS.PC.5299** is a **colloidal dispersion of bio-based oleophobic silica**, synthesized from Rice Husk and used as a Multifunctional Additive for multiple applications based on **Aqueous systems**.

# **Product Benefits**

- Repels oils, hydrocarbon fluids, water, lubricating oils, petroleum products etc.
- Improvement in hydrophobic and oleophobic properties for aqueous coatings and treatments.
- · East to clean/self cleaning effect
- Improvement in substrate wetting, water resistance, blush resistance, Anti-blocking properties and weather resistance
- Recommended for use in aqueous topcoats such as 2 component polyurethane, alkyd/melamine, polyester/melamine, acrylate/melamine and acrylate/epoxy combinations.
- Due to high surface activity, colloidal silica accumulates on the surface of the coating, and because of -OH reactivity (Primary & secondary), it can be integrated into the polymer network by reacting with suitable binders. Hence, effects of which are maintained for a long period of time.
- Advanced material with high purity from bio-based organic source.
- Recommended dosage: 4-8% (as supplied on total formulation weight.)
- Incorporation: Oleophobic colloidal silica should be added towards the end of the production process and incorporated in the coating at a sufficient shear rate.

Properties		
PROPERTIES	UNIT	SPECIFICATION
State	1888 <del>-</del> 588	Colloidal dispersion
Appearance	//// <del>-</del> ////	Translucent White
Nonvolatile matter (150°C, 10 minutes)	%	approx. 32%
Density*	g/cm <sup>3</sup>	0.8 - 1.0
OH Value (Active substance)	mg KOH/g	approx. 29

<sup>\*</sup> At time of packaging.

## **Product Information**







QMS granted by Universal GmbH

## **Packaging**

**Biosilico CS.PC.5299** is supplied in 65L HDPE drums.

# **Storage and Handling**

- Store in closed containers under dry condition, protect the material from volatile substances, and handle sensibly to minimize dust generation.
- This product should be used within 12 months from production date.

# **Safety Data**

#### Warning

- · Keep away from source of ignition to avoid spreading dust.
- · Use with adequate ventilation.
- Drying and abrasive properties may cause skin, eye or respiratory irritation.
- · Avoid inhalation or prolonged contact with skin.
- Dispose of in accordance with state and local requirement.
- See MSDS for more information.

#### First Aid

 Follow the rules of personal hygiene on dust inhalation and/or eye contact.

## After eye contact

- Remove contact lens if have.
- Flush open eyes with large quantity running water for at least 15 minutes.
- · Call for medical care if symptoms persist.

#### After skin contact

- Flush skin with water at least 15 minutes.
- · Call for medical care if symptoms persist.

#### **After inhalation**

- · Supply fresh air.
- · Call for medical care if receive complaints.
- · Do CPR if stop breathing.

## After swallowing

- Call for medical care.
- Do not induce vomiting.

