

# Joncryl<sup>®</sup> 7161

介绍	Joncryl <sup>®</sup> 7161是一支巴斯夫国产丙烯酸成膜乳液，为提升纸箱油墨和光油配方耐磨性能提供了经济有效的解决方案。
主要特点	良好的成膜性能 高耐磨 耐水
化学成分	苯丙乳液

## 性能

### 典型参数

(不作为产品规格说明书)

外观	半透明乳液
固含	46.0%
粘度 (25 °C)	600 mPa.s
pH	8.5
酸值	52 mgKOH/g
比重 (25 °C)	1.02 g/ cm <sup>3</sup>
最低成膜温度	< 0°C
玻璃化温度T <sub>g</sub>	-45°C

## Application

Joncryl<sup>®</sup> 7161 是一支高性能成膜乳液,可用于水性油墨与光油。可明显提升配方产品的耐磨性能。

Joncryl<sup>®</sup> 7161 TDS CN(preliminary)

### Safety

When handling this product, please comply with the advice and information given in the safety data sheet and observe protective and workplace hygiene measures adequate for handling chemicals.

### Note

The data contained in this publication are based on our current knowledge and experience. In view of the many factors that may affect processing and application of our product, these data do not relieve processors from carrying out their own investigations and tests; neither do these data imply any guarantee of certain properties, nor the suitability of the product for a specific purpose. Any descriptions, drawings, photographs, data, proportions, weights, etc. given herein may change without prior information and do not constitute the agreed contractual quality of the product. The agreed contractual quality of the product results exclusively from the statements made in the product specification. It is the responsibility of the recipient of our product to ensure that any proprietary rights and existing laws and legislation are observed.

© = registered trademark, ™ = trademark of the BASF Group, unless otherwise noted